

DECLARATION OF PERFORMANCE

Grundfärg Mineral

No TIK-0663-2301

1. Unique identification code of the product type: **TIK-0663-2301 Alcro Grundfärg Mineral**
2. Intended uses: **Product for the protection and repair of concrete structures – Coating: moisture control (2.2), increased resistivity by limiting moisture content (8.2)**
3. Manufacturer: **Tikkurila Oyj, P.O. Box 53, FI-01301 Vantaa**
4. System of assessment and verification of consistency of performance of the construction product: **AVCP 2+**
5. Harmonised standard: **EN 1504–2:2004**

Notified body: **AVCP 2+: 0809 VTT Expert Services Oy**

6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Linear shrinkage	NPD	EN 1504-2:2004
Coefficient of thermal expansion	NPD	
Adhesion by cross-cut test	NPD	
Permeability to water vapour	class I, $s_D < 5 \text{ m}$	
Capillary absorption and permeability to water	$w < 0,1 \text{ kg/m}^2 \cdot \text{h}^{0,5}$	
Adhesion after thermal compatibility	NPD	
Crack bridging ability	NPD	
Adhesion	$\geq 1,5 \text{ N/mm}^2$	
Fire classification	F (NPD)	
Slip resistance	NPD	
Behaviour after artificial weathering	NPD	
Antistatic behaviour	NPD	
Adhesion on wet concrete	NPD	
Release of dangerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

A handwritten signature in blue ink, appearing to read 'Magnus Engblom', with a long horizontal flourish extending to the right.

Magnus Engblom

Section Leader, Facade & Specialties
AC EMEA Portfolio Development Nordic
PPG Tikkurila

At Vantaa on 29.5.2024